

## "Q" Clause

## Purchase Order Attachment

Rancho Santa Margarita, CA 92688

Page 1 of 1

NUMBER:	REV:	Box Packaging Requirements for Protection of Electrostatic Sensitive Devices			
DOCUMENT OWNER: QUALITY MANAGER					
PREPARED BY: Will Distler			SIGNATURE: Will Distler	DATE: 04/11/2019	DEPT: Quality
APPROVED BY: Andrew Lawrence			SIGNATURE: Andrew Lawrence	DATE: 04/11/2019	DEPT: Quality

Packaging of electrostatic sensitive devices shall conform to the following requirements:

- Protection shall be provided to prevent physical damage and to maintain position
  of leads or terminals during handling and transportation. Material used for this
  protection shall be non-corrosive and provide protection against generation of
  static electricity. At the supplier's option, conductive shunting foam, bars or clips
  may be applied on electrical connectors to short all connector pins and the
  connector shell together.
- All electrostatic sensitive devices shall be contained in individual antistatic or conductive foam padded sleeves or boxes.
- Shipping containers shall then be enclosed in an ESD protective material conforming to MIL-B-81705, Type 1. This is to provide protection from electrostatic sources of at least 4,000 volts in the form of field induction or direct discharge.
- Any packing dunnage shall be of the antistatic variety.
- Both internal and external packaging containers shall be marked with a caution label as shown below or an appropriate equivalent.



Note: Failure to comply with these packaging requirements will result in rejection of the entire lot of devices at Receiving Inspection.